

**FUJIPA** FUJIPLA®

**Let's LAMIPACK it!**

For professionals

For posters, sign boards

For menu cards, price cards

For catalogues, documents

For wider printed materials

# Powerful! Full-scale Output!

Advanced models of LPP1051/6509  
Laminating width widened \*LPP1112  
Always an excellent finish guaranteed  
Easy operation acquired

The maximum laminating width of  
1120mm enables wider lamination.  
Also good for cold lamination,  
with the optional Rewinder. \*LPP1112



Rear Cutter

Operation Panel



Hot LAMINATOR

Fuji Lamipacker®

**LPP6512** max.width  
650mm

A1 size

Hot & Cold LAMINATOR

Fuji Lamipacker®

**LPP1112** max.width  
1120mm

Perfect Choice as a Professional Laminator



## Perfect Choice as a Professional Laminator

Hot & Cold LAMINATOR

**LPP6512** max.width **650**mm **A1** size

**LPP1112** max.width **1120**mm

### Features

- Max. laminating width is 1120mm for LPP1112 and 650mm for LPP6512.
- Our excellent heating system enables consistently first-class lamination.
- Paper core sizes: 2-1/4 inch, 3 inch for LPP1112  
1 inch, 2-1/4 inch, 3 inch for LPP6512
- Cold lamination is also possible with the optional Rewinder.
- With combination of temperature control and speed control, almost all kinds of lamination is possible.
- Precise setting is possible with Digital Panel.
- Stand-by mode saves power consumption.
- By using thinner film, such as 32 mic, you can save on running costs.

### Specifications

Model	LPP6512	LPP1112
Max. laminating width	650mm(A1)	1120mm
Max. laminating thickness	0.8mm	
Laminating speed	0.6 - 1.8m/min.	
Temperature range	Room temperature, 50 - 130 °C	
Power consumption	2000W	2933W
Power supply	AC 220-240V(50/60Hz)	
Dimensions	850(W)x500(D)x402(H)mm	1471(W)x500(D)x402(H)mm
Weight	80.0kg	107.0kg
JAN(EAN)Code	4514015200370	4514015200387
Attachment	Film Setting Board Stand	Film Setting Board Stand
Option		Rewinder

\*Specifications may be modified without prior notice.

**Advanced models of LPP6509/1051**  
**Laminating width widened**  
**Easy operation acquired**  
**Always an excellent finish guaranteed**

### Laminating Film

- It is recommended to use our original roll film. Mismatching of film characteristics may lead to problems such as jamming or imperfect lamination.
- By choosing our lamination film, it is possible to obtain not only waterproof effect but also UV cut or anti-static effect.

### Safety Precautions

- Please read instruction manual thoroughly before operation to avoid danger to yourself and failure in the lamination process.
- Should any of the following symptoms occur, unplug the Lamipacker and contact your Fujipla dealer.
  - ★ The power cord or plug gets unusually hot.
  - ★ A strange smell or smoke comes out of the machine.
  - ★ Water or a foreign substance gets inside the machine
- Warning and caution labels are omitted on the photos in this catalogue.
- Specifications or appearance of the product may change for improvement reasons without notice.
- Parts for maintenance service are available for a minimum of 5 years after cessation of the manufacture of product.

This catalogue is valid as of January 2006.