



Scriptel® ScripTouch® Slimline 1X5 USB ST1475 ProScript Device Interface

Key Features

- Slim design with wide palm rest
- Active battery-less tethered pen
- Horizontal snap-in and vertical pen mounts
- Bottom-side rubber feet and mounting holes
- Durable plastic case construction with heavy-duty cable attachments



Specifications

Active Signature Area	1.13" x 4.25" (28.7 x 108.0mm)
Signature Display	Not on signature pad, signature rendered on host
Pen Type	Active battery-less tethered pen
Sensing Technology	Scriptel StaticCap capacitive sensing
Min Signature Resolution	500ppi
Min Signature Sampling Rate	120pps
Product Dimensions	6" x 5.375" x 0.95" (152.4 x 136.5 x 24.1mm)
Data Interface	USB 2.0 (standard A-type connector)
Data Protocol	Scriptel ProScript device interface
Power Supply	USB bus-powered, no separate external power supply needed
Operating Systems	Support available for Windows, Mac OS, Linux
Development Environments	.NET, JavaScript, Java, PHP, WebSockets and others on request
Downloadable Software	ScripTouch Sign and Save, ScripTouch Toolbox, OmniScript universal signature integration platform, Word, Excel and Adobe plugins
Warranty	2 Year

Ruggedly Reliable

Software Excellence

ProScript Interface
Extensive SDKs
Supports OmniScript

Application types
• Locally-installed
• Remote server-based

StaticCap™ sensing
Long lifetime pen
>1 million signatures

2 Year Warranty